



LED / Focus configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Anodized, High Strength Aluminium
Case Color:	Anthracite Dark Grey
Switch:	Quality Tested Metal Switch With Touch Function -Switch At Rear
Dimensions:	L: 127.7mm, ø: 26.5mm
Weight incl. battery:	139g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature:	-20°C to +35°C
Built in Controller:	YES, 5-step controller by press or touch
Standard Power Source:	Li-ion 18650 (8.14 Wh) 2 pcs. included
Beam / Distance:	Variable from Spot to Floodlight / 245 Meters
Luminous Flux: Max: 50	00 lm / High: 250 lm / Medium: 50 / Low: 15 Lumen / Stroboskop 10 Hz
Lighting Time:	Max: 2h / High: 3h / Medium: 15h / Low: 89h
Accessories included:	Pro. Quality Pouch with Velcro and Press Stud, Strap,
	100-240VAC Adaptor with USB cable and external ICR 18650 Charger
Customs Tariff Number:	8513 1000
Packaging:	Presentation tube
Single Box Content / Size / Weight:	1 pcs, height/diameter, 18 x 9,7 cm / 390 g
Master Box Content / Size / Weight:	32 pcs, 41 x 41 x 39.5 cm / 14.5 kg
Order's Adress:	info@suprabeam.com

Barcode and part number, varies by language, contact Suprabeam for information.

